uPVC Bi-Fold Door Order



Customer Name:					Please e	nail to :	info@a	alumate.co.uk
Tel No:	Your Reference:			Or Fax to: 01443 523544				
Fax No:		—— Date Requesto	ed:		'	ax to: u	1443 5.	23544
Main Colour:	Opening:	Cill:	Glazing Option	ns:	Add On:	15mm	25mm	50mm
Single Colour	☐ - Open Out	☐ - None	☐ - Toughene	☐ - Toughened A Rated Spec Glass		т 🗆		
☐ - White	☐ - Open In *	□ - 85mm	☐ - Toughene	☐ - Toughened C Rated Spec Glass				
☐ - Cream		□ - 150mm	☐ - Unglazed			L \square		
☐ - White Ash	Hinge Colour:	□ - 180mm	☐ - Glass to			R □		
☐ - Golden Oak	☐ - Black	□ - 190mm	A Rated Spec-	—softcoat+ warmedge black argor	_ n			
☐ - Irish Oak	☐ - White	30mm Deduction uPVC	C Rated Spec-	-softcoat+ silver spacer				
☐ - Rosewood	☐ - Grey Silver	Drainage:			Trickle Ve	nt:		
Dual Colour (External/Internal)	☐ - Champagne *** ☐ - Satin Silver ***	☐ - Concealed ☐ - Face			Note: 50m □ - No Tric			e quired Add-On
\square - Anthracite Grey / White	☐ - Chrome ***	☐ - No Drainage						
☐ - Black Ash / White	Shootbolt Handles:				Width			
☐ - Golden Oak / White	☐ - Black				(inc any add-on):			
☐ - Irish Oak / White	☐ - White	Dimensions and configuration:			· · · · · · · · · · · · · · · · · · ·	1		
☐ - Rosewood / White	☐ - Grey Silver			←		J —		
☐ - White Ash / White	☐ - Champagne ***		Height †	: 1 1	······	T	·r····	:
☐ - Other Special	☐ - Satin Silver *** ☐ - Chrome ***	(i	nc any cill/add-on):					
Ali Low Threshold :	Traffic Door Handles Colour:	L					i	
☐ - Part M (27mm) *	☐ - Black		ı					
☐ - Internal Use (15mm) **	☐ - White		1					
	☐ - Grey Silver		•	When viewed from outside				
* Reduced Weather Proofing	☐ - Champagne ***			= Leaf Opening Direct	ction	= Traffic	Door Poi	nting to Hinge
** Allows air and noise through door	☐ - Satin Silver ***							3 0

*** Note additional cost of these items

☐ - Chrome ***

Please note an even number of panes in one direction will not have a traffic door. Please ask if unsure.