Aluminium Bi-Fold Door □Order □Quote Request Your Reference: **Customer Name:** Please email to: info@alumate.co.uk Tel No: Date Requested: Or Fax No: Fax to: 01443 523544 Main Colour: Opening: Trickle Vent Required in 40mm Head Add-On: Add On: Top Bottom Left Right ☐ - White / White ☐ - Open Out ☐ - Qty of Trickle Vent(s) in Head Add-On ☐ - Anthracite Grey / Anthracite Grey 20mm ☐ - Open In (*Note*: less weather proof) 40mm ☐ - Black / Black Width Cill: ☐ - Brown / Brown (inc any add-on): ☐ - None □ - 95mm ☐ - Anthracite Grey / White □ - 150mm ☐ - Black / White ☐ - 177mm ☐ - Other..... Height □ - 190mm Note: 25mm Deduction (inc any cill/add-on): Hinge Colour: Drainage: ☐ - Black (recommended on all colours) ☐ - Concealed ☐ - White ☐ - Face ☐ - Silver ☐ - No Drainage **Glazing Options:** Shootbolt T – Handle: When viewed from outside ☐ - Toughened A Rated Spec Glass ☐ - Black = Traffic Door Pointing to Hinge = Leaf Opening Direction ☐ - Toughened C Rated Spec Glass ☐ - White ☐ - Silver ☐ - Unglazed Points to note: ☐ - Glass to ☐ - Chrome (*note*: cost addition) Min Sash Width: 650mm A Rated Spec—softcoat+ warmedge black argon Max Sash Width: 1200mm wide (Leaf height and wind loading dependant) C Rated Spec—softcoat+ silver spacer Max Sash Height: 3000mm (not recommended over 2400mm) **Traffic Door Handle Colour (where fitted):** An even number of leaves all opening in one direction will not have exter-☐ - Black Threshold: nal access when closed (no traffic door) ☐ - White ☐ - 54mm Standard Black hinges recommended on all colours due to black inter-leaf gasket

Assistance is needed on-site to aid delivery driver unloading products

☐ - 34mm (Reduced Weather Proofing)

☐ - 22mm (Internal Use Only)

☐ - Silver

☐ - Chrome (note: cost addition)