uPVC Bi-Fold Door □Order □Quote Request

☐ - Chrome ***

*** Note additional cost of these items



Customer Name:	er Name:						Please email to : info@alumate.co.uk			
Tel No:	Tel No: Your Reference:				Or Fax to: 01443 523544					
Fax No:		Date Requested	:		r	ax to: 0	1443 5	23544		
Main Colour:	Opening:	Cill:	Glazing Options:		Add On:	15mm	25mm	50mm		
Single Colour	☐ - Open Out	□ - None	☐ - Toughened A F		т 🗆					
☐ - White	☐ - Open In *	□ - 85mm	☐ - Toughened C F		в 🗆					
☐ - Cream		□ - 150mm	☐ - Unglazed			L \square				
☐ - White Ash	Hinge Colour:	□ - 180mm	☐ - Glass to			R □				
☐ - Golden Oak	☐ - Black	□ - 225mm	A Rated Spec—sof	ftcoat+ warmedge black argon						
☐ - Irish Oak	☐ - White	30mm Deduction uPVC	C Rated Spec—soft	tcoat+ silver spacer						
☐ - Rosewood	☐ - Grey Silver	Drainage:			Trickle Ver	nt:				
	☐ - Champagne ***	☐ - Concealed			Note: 50m	m Head A	dd-On R	equired		
Dual Colour (External/Internal)	☐ - Satin Silver ***	□ - Face			☐ - Qty Trickle Vents in Head Add-On					
☐ - Anthracite Grey / White	☐ - Chrome ***	☐ - No Drainage								
☐ - Black Ash / White	Shootbolt Handles:				Width					
☐ - Golden Oak / White	☐ - Black			(in	c any add-on):					
☐ - Irish Oak / White	☐ - White	Dimensions and configuration:				7				
☐ - Rosewood / White	☐ - Grey Silver		•			J —		→		
☐ - White Ash / White	☐ - Champagne ***		♦ £			· · · · · ·	· : · · · ·	··•		
☐ - Other Special	☐ - Satin Silver ***		Height							
·	☐ - Chrome ***	(inc	any cill/add-on):							
Ali Low Threshold :	Traffic Door Handles Colour:									
☐ - Part M (27mm) *	☐ - Black		i i				•			
☐ - Internal Use (15mm) **	☐ - White		. ↓ i				•			
	☐ - Grey Silver		√ %• Ι	Nhen viewed from outside	······					
* Reduced Weather Proofing	☐ - Champagne ***		_	= Leaf Opening Direction		= Traffic	Door Po	nting to Hinge		
** Allows air and noise through door	☐ - Satin Silver ***			- Lear Opening Direction			200110			

Please note an even number of panes in one direction will not have a traffic door. Please ask if unsure.